

Spesifikasi Utama

(Melainkan jika dinyatakan sebaliknya, $T_a = 25^\circ\text{C}$)

Nombor bahagian	Julat pengendalian			Ciri elektrik				Jenis pengendalian pemulihan	Ciri-ciri lain	Pemeriksaan & Pembelian Stok
	Voltan masukan	Suhu simpangan pengendalian	Arus elektrik keluaran	Ketepatan had arus lampau:	Pengapit voltan lampau	Masa respons litar pintas	Masa respons had arus elektrik			
	V_{IN}	T_{j_opr}	I_{OUT}	I_{LIM} ketepatan	V_{OVC}	t_{SHORT}	t_{LIM}			
	(V)	($^\circ\text{C}$)	(A)	(%)	(V)	(μs)	(μs)			
			Minimum/Maksimum	Tipikal	Tipikal	Tipikal				
TCKE903NL								Diselak		Beli Dalam Talian
TCKE903NA [1]				3.87				Cuba semula secara automatik		-
TCKE905NL [1]								Diselak		-
TCKE905ANA	2.7	-40 hingga 125	0 hingga 4.0	-17/ + 14 [2]	5.7	2.0	80	Cuba semula secara automatik	Fungsi BENDERA	Beli Dalam Talian
TCKE912NL [1]	23.0							Diselak		-
TCKE912NA [1]					13.7			Cuba semula secara automatik		-
TCKE920NL [1]								Diselak		-
TCKE920NA [1]					22.2			Cuba semula secara automatik		-