

Spesifikasi Utama

(@T<sub>a</sub>=25 °C)

Nombor bahagian	Pakej		Konfigurasi	Penarafan maksimum mutlak	Voltan balikan kerja puncak V <sub>RWM</sub> maksimum (V)	Jumlah kapasitans C <sub>t</sub> @V <sub>R</sub> =0 V (pF)		Kapasitans dinamik R <sub>DYN</sub> jenis @I <sub>PP1</sub> =8 A hingga I <sub>PP2</sub> =16 A <sup>[3]</sup> (Ω)	Pengapit voltan V <sub>C</sub> maksimum @I <sub>PP</sub> =2 A <sup>[4]</sup> (V)	Semakan Stok & Pembelian
	Nama (Kod pakej)	Jenis saiz (mm)		Voltan nyahcas elektrostatik V <sub>ESD</sub> <sup>[2]</sup> (kV)		jenis	maksimum			
<a href="#">DF2B5M4ASL</a>	SL2 (SOD-962)	0.62×0.32× 0.3	Dwiarah	±16	3.6	0.15	0.2	0.7	15	<a href="#">Beli Dalam Talian</a>
<a href="#">DF2B6M4ASL</a>				±15	5.5	0.15	0.2	0.7	15	<a href="#">Beli Dalam Talian</a>